20000 liters tank in Stainless 304

232 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 20.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Top type: conical

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 4 adjustable feet

Insulation material: rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Height manhole 1 (mm): 420 mm
Tank outlet: inside Ø 80 mm
Total outlet valve: no
Agitator: yes

Agitator type: tripad
Position engine: at the top
Number of revolutions: 31 / 62
Power: 3,30
Voltage: three-phase

Insulation body: yes
Insulation bottom/sides: yes
finish of the outer jacket: welded
Insulation thickness: 60
Internal diameter tank: 2.860 mm

Distance from outlet to ground: 500 mm
Outer diameter tank: 2.980 mm
Cylinder height: 3.200 mm
Total height of tank: 5.900 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Empty weight tank: 1.950

SKU: 381725

Mer information

Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: insulated
Mobile Tank: No, it is not.
Övrig information: we can't give any guarantees about the agitator
Agitator: Yes
Tank Shape: cylindrical
Complete Drainage: Yes
Bottom Type: conical
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 20000

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 80 mm
Technical Drawing Available: No, it is not.
Outlet Valve: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304
Insulation material: Rockwool
Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 3.200 mm
Internal diameter: 2,860 mm
Outlet Height to Ground: 500 mm
Total Height: 5.900 mm
Outer diameter: 2,980 mm

Stirrer

Power (kW): 3,30
Motor Position: at the top
Agitator Type: tripad
Speed (RPM): 31 / 62
Voltage: three-phase

Outer Cladding and Insulation Thickness

External jacket finish: welded
Insulation bottom/end caps: Yes
Jacket insulation: Yes
Insulation material: Rockwool

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer

Insulation Thickness OW: 60
Isolated: Yes
Weight: 1.950

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor