20000 liters tank in Stainless 304

202 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 20.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Bottom outlet: yes
Total discharge: yes

Fixation points: 3 adjustable feet
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Hinged lid: yes
Tank outlet: inside Ø 50 mm
Agitator: yes
Agitator type: propeller agitator

Position engine: at the top
Power: 1,20
Voltage: 400 V - three-phase
Current: 4,20
Distance from outlet to ground: 500 mm

Outer diameter tank: 3.260 mm
Cylinder height: 2.535 mm
Total height of tank: 4.450 mm
Empty weight tank: 1.950

SKU: 417479

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: insulated
Mobile Tank: No, it is not.
Övrig information: we can't give any guarantees about the agitator
Agitator: Yes
Tank Shape: cylindrical
Complete Drainage: Yes
Bottom Type: conical
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 20000

Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tank Dimensions

Cylinder Height: 2.535 mm
Outlet Height to Ground: 500 mm
Total Height: 4,450 mm
Outer diameter: 3.260 mm

Stirrer

Power (kW): 1,20
Motor Position: at the top
Agitator Type: propeller agitator
Voltage: 400 V – three-phase

Mer

Isolated: Yes
Weight: 1.950

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor