

20300 liter tank in Acid-proof 316



350 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K3-IL

Volumetric volume (L): 20.300 L

Max. density P (kg/m³): 1.200

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: adjustable feet

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 316

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes



Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2,50 mm

Bottom: 3 mm

Internal diameter tank: 2.400 mm

Distance from outlet to ground: 306 mm

Outer diameter tank: 2.514 mm

Cylinder height: 4.250 mm

Total height of tank: 5.400 mm

Empty weight tank: 1.649

SKU: 569390

Mer information



Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank: ATM – atmospheric
Configuration: insulated
Max. Service Temperature: 100 °C
Maximum Product Density: 1200
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Agitator: No
Tank Shape: cylindrical
Complete Drainage: Yes
Bottom Type: conical 15 °
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 20300

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Technical Drawing Available: Yes

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L
Insulation material: Rockwool
Exterior cladding: RVS 304L



Tank Dimensions

Cylinder Height: 4.250 mm

Internal diameter: 2,400 mm

Outlet Height to Ground: 306 mm

Total Height: 5,400 mm

Outer diameter: 2.514 mm

Tjocklek på tank

Bottom: 3 mm

Cylinder: 2,50 mm

Top: 2,50 mm

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Isolated: Yes

Weight: