20300 liters tank in Stainless 304

209 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K5-SL
Additional information: inner surface 0.8µ
Volumetric volume (L): 20.300 L
Max. density P (kg/m³): 1.350
Ra inner weld: 0,80

Finish stainless steel: 2B
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 100 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 304L (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: conical 15 °
Shape of tank: cylindrical
Bottom type: conical 15 °
Total discharge: yes
Fixation points: 5 adjustable feet

Manway(s): RVS 304L
Gasket manway(s): EPDM
Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Inspection of: TUV
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 500 mm
CIP spray ball: no, optional
Tank outlet: inside Ø 65 mm
Outlet type: DIN11851 male

Total outlet valve: no, optional
Agitator: no, optional
Top: 2,50 mm
Cylinder: 2 mm
Bottom: 3 mm

Distance from outlet to ground: 356 mm
Outer diameter tank: 2.400 mm
Cylinder height: 4.250 mm
Height of top: 397 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Feet height: 744 mm

Total height of tank: 5.390 mm
Empty weight tank: 900

SKU: 454484

Mer information

Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank:
Stainless steel finish: 2b
Configuration: single-skin
Max. Service Temperature: 100 °C
Maximum Product Density: 1350
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Övrig information: inner surface 0.8µ
Agitator: No
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: conical 15 °
Heating / Cooling: No
Contact Surface: SS AISI 304L (V2A)
Volume in liters: 20300

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Equipment
Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 65 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male

Material Overview
Material: Stainless steel 304
Fixing point(s): RVS 304L

Tank Dimensions
Cylinder Height: 4.250 mm
Height on legs: 744 mm
Outlet Height to Ground: 356 mm
Total Height: 5.390 mm
Outer diameter: 2,400 mm

Tjocklek på tank
Bottom: 3 mm
Cylinder: 2 mm
Top: 2,50 mm

Mer
Isolated: No
Weight: 900

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor