2050 liters tank in Stainless 304

71 000 SEK /st exkl moms

Additional information: Cosmetics; some residues of previous content
Volumetric volume (L): 2.050 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no

Total discharge: yes
Volume: 25 L
Max Overpressure: 2 Bar
Max. working temperature: 80 °C
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: DN50 DIN 11851

Agitator: yes
Number of revolutions: 1.440
Power: 5,50
Internal diameter tank: 1.430 mm
Cylinder height: 1.250 mm

Total height of tank: 2.600 mm

SKU: 428525

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: single jacketed with heat-exchanger
Max. Service Temperature: 80 °C
Mobile Tank: No, it is not.
Övrig information: Cosmetics; some residues of previous content; we can't give any guarantees about the agitator
Agitator: Yes
Complete Drainage: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 2050

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.250 mm
Internal diameter: 1.430 mm
Total Height: 2.600 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Stirrer
Power (kW): 5,50
Speed (RPM): 1.440

Mer
Isolated: No