2068 liters tank in Acid-proof 316

266 000 SEK /st exkl moms

Additional information: pharmacy; Outlet fitting incomplete; ; some residues of previous content
Volumetric volume (L): 2.068 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 160 L
Max Overpressure: 4 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 44

Cylinder: 4 mm
Internal diameter tank: 1.284 mm
Outer diameter tank: 1.550 mm
Cylinder height: 1.200 mm
Total height of tank: 2.550 mm

SKU: 425597

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 150 °C
Mobile Tank: No, it is not.
Övrig information: pharmacy; outlet fitting incomplete;; some residues of previous content; we can't give any guarantees about the heating/cooling jacket
Agitator: No
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 2068

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions
Cylinder Height: 1.200 mm
Internal diameter: 1.284 mm
Total Height: 2,550 mm
Outer diameter: 1.550 mm

Tjocklek på tank
Cylinder: 4 mm

Mer
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor