

210 liter tank in Syrefast 316



53 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: The tank has never been used, in absolute new condition, New agitator.; we can't give any guarantees about the agitator

Volumetric volume (L): 210 L

Ra inner weld: 0,80



Finish stainless steel: 2B

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Bottom type: flat

Total discharge: yes

Fixation points: 3 adjustable feet

Fixation point(s): RVS 304L

Wet parts agitator(s): SS AISI 316L (V4A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 1.400

Power: 0,75

Voltage: mono

Cylinder: 2 mm

Bottom: 2 mm

Internal diameter tank: 595 mm

Distance from outlet to ground: 260 mm

Outer diameter tank: 705 mm

Cylinder height: 770 mm

Total height of tank: 1.460 mm

Empty weight tank: 60

SKU: 383795

Mer information

Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Stainless steel finish: 2b

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: The tank has never been used, in absolute new condition, New agitator; we can't give any guarantees about the agitator

Agitator: Yes

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: flat

Heating / Cooling: No

Contact Surface: SS AISI 316L (V4A)

Volume in liters: 210



Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 40 mm
Technical Drawing Available: No, it is not.
Outlet Type: DIN11851

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L
Material vätskeberörd del på omrörare: SS AISI 316L (V4A)

Tank Dimensions

Cylinder Height: 770 mm
Internal diameter: 595 mm
Outlet Height to Ground: 260 mm
Total Height: 1.460 mm
Outer diameter: 705 mm

Stirrer

Power (kW): 0,75
Motor Position: at the top
Agitator Type: propeller agitator
Speed (RPM): 1.400
Voltage: mono

Tjocklek på tank

Bottom: 2 mm
Cylinder: 2 mm



Mer

Isolated: No

Weight: 60