

2171 liter tank in Syrafast 316



135 000 SEK /st exkl moms

Additional information: Confectionery industry; Outlet 1 block flange diameter pipe inside 80 mm with flanged, tapering fitting; slight metallic discoloration inside the tank; dents at the insulation jacket

Volumetric volume (L): 2.171 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 158 L

Max Overpressure: 2,50 Bar

Max. working temperature: 90 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Number of revolutions: 14

Power: 2,20

Internal diameter tank: 1.880 mm

Outer diameter tank: 2.090 mm

Cylinder height: 510 mm

Total height of tank: 2.100 mm

SKU: 402005



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Max. Service Temperature: 100 °C

Mobile Tank: No, it is not.

Övrig information: Confectionery industry; Outlet 1 block flange diameter pipe inside 80 mm with flanged, tapering fitting; slight metallic discoloration inside the tank; dents at the insulation jacket; we can't give

Additional Information2: any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 2171

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 510 mm
Internal diameter: 1.880 mm
Total Height: 2.100 mm
Outer diameter: 2,090 mm

Stirrer

Power (kW): 2,20
Speed (RPM): 14

Mer

Heat Exchanger: RVS 304
Isolated: Yes