

22000 liters tank in Stainless 304



211 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 22.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 85 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no



Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 adjustable feet

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 2

Position of manway: cylinder

Height manhole 1 (mm): 420 mm x H 305 mm

Position 2nd manway: at the top

Height manhole 2 (mm): 420

Tank outlet: inside Ø 80 mm

Total outlet valve: no

Agitator: yes

Agitator type: propeller agitator

Position engine: in the cylinder

Number of revolutions: 69 / 142

Power: 2,20

Voltage: three-phase

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded

Insulation thickness: 50

Internal diameter tank: 2.900 mm



Distance from outlet to ground: 600 mm

Outer diameter tank: 3.000 mm

Cylinder height: 3.550 mm

Total height of tank: 5.100 mm

Empty weight tank: 1.500

SKU: 381695

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Max. Service Temperature: 85 °C

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 22000



Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 80 mm
Technical Drawing Available: No, it is not.
Outlet Valve: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304
Insulation material: Rockwool
Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 3,550 mm
Internal diameter: 2,900 mm
Outlet Height to Ground: 600 mm
Total Height: 5.100 mm
Outer diameter: 3,000 mm

Stirrer

Power (kW): 2,20
Motor Position: in the cylinder
Agitator Type: propeller agitator
Speed (RPM): 69 / 142
Voltage: three-phase

Outer Cladding and Insulation Thickness

External jacket finish: welded
Insulation bottom/end caps: Yes
Jacket insulation: Yes
Insulation material: Rockwool



Mer

Insulation Thickness OW: 50

Isolated: Yes

Weight: 1.500