

2210 liter tank in Stainless 304



68 000 SEK /st exkl moms

Additional information: Food industry; 4 stainless steel 304 claws; manhole diameter approx. 420 mm; insulation only around the cylinder; the two vessels were placed in a stainless steel frame by the previous operator; this frame is still available and can be supplied at extra cost on request (see photos)

Volumetric volume (L): 2.210 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 90 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN65

Agitator: yes

Number of revolutions: 39

Power: 1,50

Internal diameter tank: 1.290 mm

Outer diameter tank: 1.420 mm

Cylinder height: 1.450 mm

Total height of tank: 2.550 mm

SKU: 425216

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Max. Service Temperature: 90 °C

Mobile Tank: No, it is not.

Övrig information: Food industry; 4 support brackets, Aisi 304; Manhole diameter approx. 420 mm; Insulation around the cylinder only; The previous operator had the two tanks in a stainless steel frame; This frame is

Additional Information2: still available and can be included upon request for an additional charge (see photos); we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 2210

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.450 mm

Internal diameter: 1.290 mm

Total Height: 2,550 mm

Outer diameter: 1,420 mm



Stirrer

Power (kW): 1,50

Speed (RPM): 39

Mer

Isolated: Yes