225 liter tank in Acid-proof 316

133 000 SEK /st exkl moms

Additional information: Chemistry; 4-legged frame made of stainless steel 304; diameter of hand hole approx. 155 mm; some residues of previous content
Volumetric volume (L): 225 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 1 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 95 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 60 L
Max Overpressure: 4 Bar

Max. working temperature: 95 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 25
Agitator: yes
Number of revolutions: 156 - 838

Power: 0,75
Internal diameter tank: 590 mm
Outer diameter tank: 800 mm
Total height of tank: 2.400 mm

SKU: 429059

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 95 °C
Mobile Tank: No, it is not.
Övrig information: Chemistry; 4-legged frame, Aisi 304; Hand hole diameter approx. 155 mm; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees
Additional Information2: about the agitator
Agitator: Yes
Overpressure: 1 bar
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 225

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions
Internal diameter: 590 mm
Total Height: 2,400 mm
Outer diameter: 800 mm

Stirrer
Power (kW): 0,75
Speed (RPM): 156 – 838

Mer
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor