

## 2263 liters tank in Acid-proof 316



189 000 SEK /st exkl moms

**Additional information:** 1 immersion sleeve for PT 100 probe inside the tank

**Volumetric volume (L):** 2.263 L

**Pressure in tank:** ATM - atmospheric

**Max. temperature (°C):** 120 °C



**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 16 L

**Max Overpressure:** 4 Bar

**Max. working temperature:** 120 °C

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** yes

**Position of manway:** headside

**Outlet of tank:** DN50 DIN 11851

**Top:** 2,50 mm

**Cylinder:** 3 mm

**Bottom:** 3 mm

**Internal diameter tank:** 1.430 mm

**Outer diameter tank:** 1.640 mm

**Cylinder height:** 1.250 mm

**Total height of tank:** 2.330 mm

**Empty weight tank:** 750

**SKU:** 419264

## Mer information

### Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Max. Service Temperature: 120 °C

Mobile Tank: No, it is not.

Övrig information: 1 immersion sleeve for PT 100 probe inside the tank; we can't give any guarantees about the heating/cooling jacket

Agitator: No

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 2263

### Equipment

Product Dokument finns: No, it is not.

Agitator flange: Yes

Nameplate: Yes

Technical Drawing Available: No, it is not.

### Material Overview

Material: Acid-resistant 316

### Tank Dimensions

Cylinder Height: 1.250 mm

Internal diameter: 1.430 mm

Total Height: 2,330 mm

Outer diameter: 1.640 mm



## **Tjocklek på tank**

Bottom: 3 mm

Cylinder: 3 mm

Top: 2,50 mm

## **Mer**

Isolated: Yes

Weight: 750