

2280 liter tank in Acid-proof 316



203 000 SEK /st exkl moms

Additional information: pharmacy; foot plates made of plastic; 1 heating connection cut off; suspension of the manhole cover incomplete; bump at the insulation jacket; pipe end cut flush

Volumetric volume (L): 2.280 L

Pressure in tank: pressure

Max. pressure (Bar): 3 Bar



Max. temperature (°C): 143 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 120 L

Max Overpressure: 4 Bar

Max. working temperature: 151 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 38

Agitator: yes

Number of revolutions: 1.460

Power: 15

Internal diameter tank: 1.400 mm

Outer diameter tank: 1.570 mm

Cylinder height: 1.100 mm

Total height of tank: 2.800 mm

SKU: 391886



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: insulated with heat-exchanger

Max. Service Temperature: 143 °C

Mobile Tank: No, it is not.

Övrig information: pharmacy; foot plates made of plastic; 1 heating connection cut off; suspension of the manhole cover incomplete; bump at the insulation jacket; pipe end cut flush; we can't give any guarantees about

Additional Information2: the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 3 bars

Complete Drainage: Yes

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 2280

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1.100 mm
Internal diameter: 1.400 mm
Total Height: 2,800 mm
Outer diameter: 1.570 mm

Stirrer

Power (kW): 15
Speed (RPM): 1.460

Mer

Heat Exchanger: RVS 304
Isolated: Yes