

230 liter tank in stainless steel 304



83 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: we can't give any guarantees about the heating/cooling jacket

Volumetric volume (L): 230 L

Pressure in tank: pressure

Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no



Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 casters

Type of HE on the cylinder: dimple-jacket

Position HE: top side of the cylinder

Heat exchanger: RVS - 304 with rockwool insulation

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304L

Spray ball: RVS 304L

Valve: RVS 304

Gasket shut-off valve (mat): unknown

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

CIP spray ball: yes

Tank outlet: inside Ø 38 mm

Total outlet valve: yes

Internal diameter tank: 607 mm

Distance from outlet to ground: 195 mm

Outer diameter tank: 777 mm

Cylinder height: 750 mm

Total height of tank: 1.775 mm

SKU: 439361



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: isolert med varmeveksler

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket

Agitator: No

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: strong conical

Heating / Cooling: Yes

Contact Surface: SS AISI 304L (V2A)

Volume in liters: 230

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Tank Outlet: inside Ø 38 mm

Technical Drawing Available: No, it is not.

Outlet Valve: Yes

Material Overview

Material: Stainless steel 304

Insulation material: Rockwool

Exterior cladding: RVS 304L



Tank Dimensions

Cylinder Height: 750 mm

Internal diameter: 607 mm

Outlet Height to Ground: 195 mm

Total Height: 1.775 mm

Outer diameter: 777 mm

Heat exchangers

Position värmeväxlare: top side of the cylinder

Type of Heat Exchanger on Cylinder: dimple jacket

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Heat Exchanger: RVS – 304 with rockwool insulation

Isolated: Yes