

23000 liters tank in Stainless 304



143 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 23.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 8 non adjustable feet

Type HE: coil on the bottom inside the tank

Heat exchanger: RVS 304

Insulation material: Rockwool

Manway(s): RVS 304

Gasket manway(s): unknown

Valve: RVS 304

Gasket shut-off valve (mat): unknown

Suitable for food industry: yes

Documents included: no



Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 440 mm

Hinged lid: yes

Tank outlet: inside Ø 34 mm

Total outlet valve: yes

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Top: 3 mm

Cylinder: 2,50 mm

Bottom: 3 mm

Insulation thickness: 80

Internal diameter tank: 2.650 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 2.900 mm

Cylinder height: 3.400 mm

Total height of tank: 5.200 mm

Empty weight tank: 1.650

SKU: 387986

Mer information



Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 23000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 34 mm

Technical Drawing Available: No, it is not.

Outlet Valve: Yes

Material Overview

Material: Stainless steel 304

Insulation material: Rockwool



Tank Dimensions

Cylinder Height: 3,400 mm

Internal diameter: 2,650 mm

Outlet Height to Ground: 400 mm

Total Height: 5.200 mm

Outer diameter: 2,900 mm

Stirrer

Motor Position: at the top

Agitator Type: propeller agitator

Tjocklek på tank

Bottom: 3 mm

Cylinder: 2,50 mm

Top: 3 mm

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Heat Exchanger: RVS 304

Insulation Thickness OW: 80

Isolated: Yes

Weight: 1.650