

24100 liter tank in Stainless 304



305 000 SEK /st exkl moms

Additional information: chemistry; Technical documents of an identical tank available; for this tank the techn. documents may be obtained afterwards; 1 rectangular opening approx. 500 x 600 mm in the upper bottom

Volumetric volume (L): 24.100 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 180 L

Max Overpressure: 6 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 100

Agitator: yes

Number of revolutions: 120 - 476

Power: 30

Top: 10 mm

Cylinder: 10 mm

Bottom: 12 mm

Internal diameter tank: 3.200 mm

Cylinder height: 2.450 mm

Total height of tank: 6.050 mm

SKU: 395018

Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 200 °C

Mobile Tank: No, it is not.

Övrig information: chemistry; Technical documents of an identical tank available; for this tank the techn. documents may be obtained afterwards; 1 rectangular opening approx. 500 x 600 mm in the upper bottom; we can't

Additional Information2: give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 24100



Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 2,450 mm

Internal diameter: 3.200 mm

Total Height: 6.050 mm

Stirrer

Power (kW): 30

Speed (RPM): 120 – 476

Tjocklek på tank

Bottom: 12 mm (0,5 in.)

Cylinder: 10 mm

Top: 10 mm

Mer

Isolated: No