2420 liter tank in Acid-proof 316

233 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; Manhole DN 350/450 (manhole cover incomplete); Support ring, Fe; Flanges partially Fe
Volumetric volume (L): 2.420 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 100 L
Max Overpressure: 16 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 130

Agitator: yes
Number of revolutions: 8.2 - 41
Power: 7,50
Top: 7 mm
Cylinder: 6 mm

Bottom: 6,10 mm
Internal diameter tank: 1.400 mm
Cylinder height: 1.180 mm
Total height of tank: 3.950 mm

SKU: 405281

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: single jacketed with heat-exchanger
Max. Service Temperature: 200 °C
Mobile Tank: No, it is not.
Övrig information: Pharmaceutical chemistry; Manhole DN 350/450 (manhole cover incomplete); Support ring, Fe; Flanges partially Fe; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 3,20 bar
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 2420

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions
Cylinder Height: 1.180 mm
Internal diameter: 1.400 mm
Total Height: 3.950 mm

Stirrer
Power (kW): 7,50
Speed (RPM): 8.2 – 41

Tjocklek på tank
Bottom: 6,10 mm
Cylinder: 6 mm
Top: 7 mm

Mer
Isolated: No

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se