

2490 liters tank in Stainless 304



98 000 SEK /st exkl moms

Article type: second-hand fermentation tank

Additional information: The adjusting feet and the foot plates are missing, a new set costs 308€.; we can't give any guarantees about the heating/cooling jacket

Volumetric volume (L): 2.490 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 50 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger



Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: conical 22 °

Shape of tank: cylindrical

Bottom type: conical 22 °

Total discharge: yes

Fixation points: 4 adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: top side of the cylinder

Water pressure HE: 3 Bar

Hydraulic test pressure: 4,30 Bar

Outer jacket (ornamental wall): RVS 304

Spray ball: RVS 304

Manway(s): RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Tank outlet: inside Ø 70 mm

Total outlet valve: no, optional

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded

Insulation thickness: 80

Internal diameter tank: 1.200 mm

Distance from outlet to ground: 635 mm

Outer diameter tank: 1.360 mm

Cylinder height: 2.000 mm

Feet height: 982 mm

Total height of tank: 3.400 mm

Empty weight tank: 590

SKU: 384125

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated with heat-exchanger

Max. Service Temperature: 50 °C

Min. Operating Temperature: -10 °C

Mobile Tank: No, it is not.

Övrig information: The adjusting feet and the foot plates are missing, a new set costs 308€.; we can't give any guarantees about the heating/cooling jacket

Agitator: No

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical 22 °

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 2490



Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 70 mm
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304
Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 2,000 mm
Height on legs: 982 mm
Internal diameter: 1.200 mm
Outlet Height to Ground: 635 mm
Total Height: 3,400 mm
Outer diameter: 1.360 mm

Heat exchangers

Bottom hydrostatic test pressure: 4.30 bar
Hydrostatic test pressure: 4.30 bar
Position värmeväxlare: top side of the cylinder
Type of Heat Exchanger on Cylinder: dimple jacket
Water Pressure Heat Exchanger: 3 bars

Outer Cladding and Insulation Thickness

External jacket finish: welded
Insulation bottom/end caps: Yes
Jacket insulation: Yes



Mer

Insulation Thickness OW: 80

Isolated: Yes

Weight: 590