

250 liter tank in stainless steel 304



46 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: Top lid is missing, a new lid = 650 €.

There are two connections provided with 2 inch internal thread for mounting 2 immersion resistors with an insertion length of 500mm, the immersion resistors themselves are not included.

Volumetric volume (L): 250 L

Pressure in tank: pressure

Design pressure (Bar): 5,20 Bar

Max. pressure (Bar): 3,50 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 304L (V2A)



Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: on skirt

Type of HE on the cylinder: atmosfertical double jacket

Type of HE on the bottom: atmosfertical double jacket

Heat exchanger: RVS 304

Fixation point(s): RVS 304

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 355 mm

Tank outlet: inside Ø 32 mm

Outlet type: bsp female

Agitator: no, optional

Internal diameter tank: 695 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 795 mm

Cylinder height: 560 mm

Total height of tank: 1.370 mm

Empty weight tank: 300

SKU: 383153



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Tank design pressure: 5,20 bar

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 100 °C

Mobile Tank: No, it is not.

Övrig information: Top lid is missing, a new lid = 650 €. There are two connections provided with 2 inch internal thread for mounting 2 immersion resistors with an insertion length of 500mm, the immersion

Additional Information2: resistors themselves are not included.

Agitator: No

Overpressure: 3,50 bar

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: dish

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304L (V2A)

Volume in liters: 250



Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: Yes
Tank Outlet: inside Ø 32 mm
Technical Drawing Available: No, it is not.
Outlet Type: bsp female

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 560 mm
Internal diameter: 695 mm
Outlet Height to Ground: 400 mm
Total Height: 1.370 mm
Outer diameter: 795 mm

Heat exchangers

Type of Heat Exchanger on Cylinder: atmospheric double jacket
Bottom Heat Exchanger Type: atmospheric double jacket

Mer

Heat Exchanger: RVS 304
Isolated: No
Weight: 300