

2500 liter tank in Acid-proof 316



320 000 SEK /st exkl moms

Volumetric volume (L): 2.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1 Bar

Min. pressure (Bar): 1 Bar



Max. temperature (°C): 50 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 50 L

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Max. working temperature: 50 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN50

Agitator: yes

Number of revolutions: 18 / 35

Power: 0.44 / 0.88

Cylinder: 6 mm

Bottom: 5 mm

Internal diameter tank: 1.300 mm

Outer diameter tank: 1.455 mm

Cylinder height: 1.500 mm

Total height of tank: 3.350 mm

SKU: 403247



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: isolert med varmeveksler

Max. Service Temperature: 50 °C

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 1 bar

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 2500

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1.500 mm
Internal diameter: 1.300 mm
Total Height: 3.350 mm
Outer diameter: 1.455 mm

Stirrer

Power (kW): 0.44 / 0.88
Speed (RPM): 18 / 35

Tjocklek på tank

Bottom: 5 mm
Cylinder: 6 mm

Mer

Isolated: Yes