

2500 liter tank in Stainless 304



71 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 2.500 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no



Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 adjustable feet

Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Hinged lid: yes
Tank outlet: inside Ø 60 mm
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top

Power: 0,55
Voltage: 230 V - three-phase
Current: 2,60
Distance from outlet to ground: 860 mm
Outer diameter tank: 1.400 mm

Cylinder height: 1.475 mm
Total height of tank: 3.350 mm
Empty weight tank: 750

SKU: 417440



Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 2500

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 60 mm

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304



Tank Dimensions

Cylinder Height: 1.475 mm

Outlet Height to Ground: 860 mm

Total Height: 3.350 mm

Outer diameter: 1.400 mm

Stirrer

Power (kW): 0,55

Motor Position: at the top

Agitator Type: propeller agitator

Voltage: 230 V – three-phase

Mer

Isolated: No

Weight: 750