

2500 liter tank in Stainless 304



124 000 SEK /st exkl moms

Additional information: Double jacket in the underbody not operational

Volumetric volume (L): 2.500 L

Pressure in tank: pressure

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 50 L

Max Overpressure: 3 Bar

Max. working temperature: 140 °C

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Internal diameter tank: 1.150 mm

Cylinder height: 2.300 mm

Total height of tank: 4.000 mm

SKU: 565304

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: Food; Double jacket in the underbody not operational; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 2500

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 2.300 mm

Internal diameter: 1.150 mm

Total Height: 4,000 mm

Mer

Isolated: Yes