

25000 liters tank in Acid-proof 316



390 000 SEK /st exkl moms

Volumetric volume (L): 25.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 55 °C

Material wet parts: SS AISI 316 (V4A)



Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 489 L

Max Overpressure: 3 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN80 DIN 11851

Top: 4 mm

Cylinder: 4 mm

Bottom: 4 mm

Internal diameter tank: 2.750 mm

Outer diameter tank: 2.925 mm

Cylinder height: 4.000 mm

Total height of tank: 6.500 mm

Empty weight tank: 2.500

SKU: 483050



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Max. Service Temperature: 55 °C

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket

Agitator: No

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 25000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 4,000 mm

Internal diameter: 2,750 mm

Total Height: 6.500 mm

Outer diameter: 2.925 mm



Tjocklek på tank

Bottom: 4 mm

Cylinder: 4 mm

Top: 4 mm

Mer

Isolated: Yes

Weight: 2.500