

25500 liters tank in Stainless 304



239 000 SEK /st exkl moms

Additional information: dairy; Dented fan covers of agitators; with 1 tank the cladding panels on the agitator lantern are slightly bent; height-adjustable screws of the feet are missing (see photos); pipe end cut flush

Volumetric volume (L): 25.500 L

Pressure in tank: pressure and vacuum



Max. pressure (Bar): 0,40 Bar

Min. pressure (Bar): 0,40 Bar

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 0,40 Bar

Max onderdruk: 0,40 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 100

Agitator: yes

Number of revolutions: 16

Power: 4,40

Top: 6 mm

Cylinder: 4 mm

Bottom: 5 mm

Internal diameter tank: 2.500 mm

Outer diameter tank: 2.650 mm

Cylinder height: 5.000 mm

Total height of tank: 8.050 mm

Empty weight tank: 4.000

SKU: 410045



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: diary; Dented fan covers of agitators; with 1 tank the cladding panels on the agitator lantern are slightly bent; height-adjustable screws of the feet are missing (see photos); pipe end cut flush;

Additional Information2: we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 0,40 bar

Complete Drainage:

Vacuum Pressure: 0,40 bar

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 25500

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 5,000 mm
Internal diameter: 2.500 mm
Total Height: 8.050 mm
Outer diameter: 2,650 mm

Stirrer

Power (kW): 4,40
Speed (RPM): 16

Tjocklek på tank

Bottom: 5 mm
Cylinder: 4 mm
Top: 6 mm

Mer

Isolated: Yes
Weight: 4.000