

2580 liters tank in Stainless 304



41 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: length of the tank without cooling unit = 2950mm; Condition of the agitator is unknown, the cooling unit does not work;; we can't give any guarantees about the agitator

Volumetric volume (L): 2.580 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Shape of tank: cylindrical

Total discharge: yes

Fixation points: 4 non adjustable feet

Insulation material: PUR

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 450 mm

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: tripad

Position engine: at the top

Distance from outlet to ground: 180 mm

Total height of tank: 1.800 mm

Total outer width: 1.250 mm

Total outer length: 3.600 mm

SKU: 379883



Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Horizontal

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: length of the tank without cooling unit = 2950mm; Condition of the agitator is unknown, the cooling unit does not work,; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 2580

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 50 mm

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Insulation material: PUR

Exterior cladding: RVS 304

Tank Dimensions

Outlet Height to Ground: 180mm

Total Height: 1.800 mm

**Stirrer**

Motor Position: at the top

Agitator Type: tripad

Outer Cladding and Insulation Thickness

Insulation material: PUR

Mer

Isolated: Yes