

259 liter tank in Acid-proof 316



164 000 SEK /st exkl moms

Additional information: Diameter of hand hole 200 mm; smaller dents in the insulating jacket

Volumetric volume (L): 259 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 142 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 18 L

Max Overpressure: 3 Bar

Max. working temperature: 142 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Number of revolutions: 71 - 640

Power: 0,34

Internal diameter tank: 690 mm

Outer diameter tank: 830 mm

Cylinder height: 470 mm

Total height of tank: 2.000 mm

SKU: 421940



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 142 °C

Mobile Tank: No, it is not.

Övrig information: Pharmacy; Diameter handhole appr. 200 mm; smaller dents in the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 3 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 259

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 470 mm
Internal diameter: 690 mm
Total Height: 2,000 mm
Outer diameter: 830 mm

Stirrer

Power (kW): 0,34
Speed (RPM): 71 – 640

Mer

Isolated: Yes