

260 liter tank in stainless steel 304



54 000 SEK /st exkl moms

item available on order

Article type: brand new pressure tank - type CCT-ES-HL

Volumetric volume (L): 260 L

Max. density P (kg/m³): 1.400

Finish stainless steel: pickled

Pressure in tank: pressure

Max. pressure (Bar): 2 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger



Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical 45 °

Total discharge: yes

Fixation points: 4 non adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Number of sections: 1

Water pressure HE: 3 Bar

Steam pressure HE: 0,50 Bar

Hydraulic test pressure: 5,20 Bar

Working temperature HE cylinder: 80 °C

Heat exchanger: RVS 304

Manway(s): RVS 304L

Gasket manway(s): EPDM

Valve: RVS 304L

Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: TUV

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Tank outlet: inside Ø 32 mm

Outlet type: DIN11851 male

Total outlet valve: yes

Agitator: no



Top: 2 mm

Cylinder: 2 mm

Bottom: 2 mm

Internal diameter tank: 550 mm

Distance from outlet to ground: 180 mm

Outer diameter tank: 560 mm

Cylinder height: 970 mm

Total height of tank: 1.600 mm

Empty weight tank: 80

SKU: 378626

Mer information



Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank: pressure
Stainless steel finish: pickled
Configuration: single jacketed with heat-exchanger
Max. Service Temperature: 130 °C
Maximum Product Density: 1400
Mobile Tank: No, it is not.
Agitator: No
Overpressure: 2 bars
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: strong conical 45 °
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 304L (V2A)
Volume in liters: 260

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 32 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male
Outlet Valve: Yes

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304L



Tank Dimensions

Cylinder Height: 970 mm

Internal diameter: 550 mm

Outlet Height to Ground: 180mm

Total Height: 1.600 mm

Outer diameter: 560 mm

Heat exchangers

Vapor pressure heat exchanger: 0,50 Bar

Operating Temperature Heat Exchanger Cylinder: 80 °C

Bottom hydrostatic test pressure: 5,20 bar

Hydrostatic test pressure: 5,20 bar

Position värmeväxlare: the complete cylinder

Type of Heat Exchanger on Cylinder: dimple jacket

Water Pressure Heat Exchanger: 3 bars

Tjocklek på tank

Bottom: 2 mm

Cylinder: 2 mm

Top: 2 mm

Mer

Heat Exchanger: RVS 304

Isolated: No

Weight: 80