

27150 liters tank in Stainless 304



199 000 SEK /st exkl moms

Additional information: Seal manufacturing; Dents in the double jacket; heating coil (copper) around the cone bottom; cone height approx. 1.400 mm; 1 crane eye in the upper bottom; footplates partially bent; some residues of previous content

Volumetric volume (L): 27.150 L

Pressure in tank: ATM - atmospheric



Max. pressure (Bar): 3,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: no

Max Overpressure: 3,50 Bar

Max onderdruk: 1 Bar

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 110

Internal diameter tank: 2.790 mm

Outer diameter tank: 2.930 mm

Cylinder height: 3.450 mm

Total height of tank: 6.650 mm

SKU: 410216



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: single-skin

Max. Service Temperature: 145 °C

Mobile Tank: No, it is not.

Övrig information: Seal manufacturing; Dents in the double jacket; heating coil (copper) around the cone bottom; cone height approx. 1.400 mm; 1 crane eye in the upper bottom; footplates partially bent ; some

Additional Information2: residues of previous content

Agitator: No

Overpressure: 3,50 bar

Complete Drainage: No, it is not.

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 27150

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 3.450 mm
Internal diameter: 2,790 mm
Total Height: 6.650 mm
Outer diameter: 2,930 mm

Mer

Heat Exchanger: RVS 304
Isolated: No