280 liter tank in Acid-proof 316

137 000 SEK /st exkl moms

Additional information: Pharmacy; Air-controlled outlet valve; hand hole diameter 200 mm
Volumetric volume (L): 280 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 17 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 130 °C
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 17
Agitator: yes
Number of revolutions: 0 - 767

Power: 0,37
Internal diameter tank: 590 mm
Outer diameter tank: 720 mm
Total height of tank: 1.700 mm

SKU: 564163

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 130 °C
Mobile Tank: No, it is not.
Övrig information: Pharmacy; Air-controlled outlet valve; hand hole diameter 200 mm; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 3,20 bar
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 280

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions
Internal diameter: 590 mm
Total Height: 1.700 mm
Outer diameter: 720 mm

Stirrer
Power (kW): 0,37
Speed (RPM): 0 – 767

Mer
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor