

288 liter tank in Acid-proof 316



89 000 SEK /st exkl moms

Additional information: Heating of the double jacket by 4 electric screw-in heating elements (4.5 kW each); 1 screwed-on fitting on the spout; diameter of hand hole 150 mm

Volumetric volume (L): 288 L

Pressure in tank: ATM - atmospheric

Max. pressure (Bar): 2,50 Bar



Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 125 L

Max Overpressure: 2 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN25 DIN 11851

Agitator: yes

Number of revolutions: 91 - 640

Power: 0,37

Internal diameter tank: 790 mm

Outer diameter tank: 950 mm

Cylinder height: 500 mm

Total height of tank: 2.050 mm

SKU: 579842



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: insulated with heat-exchanger

Max. Service Temperature: 150 °C

Mobile Tank: No, it is not.

Övrig information: Heating of the double jacket by 4 electric screw-in heating elements (4.5 kW each); 1 screwed-on fitting on the spout; diameter of hand hole 150 mm; we can't give any guarantees about the

Additional Information2: heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 2,50 bar

Complete Drainage: Yes

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 288

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 500 mm
Internal diameter: 790 mm
Total Height: 2,050 mm
Outer diameter: 950 mm

Stirrer

Power (kW): 0,37
Speed (RPM): 91 – 640

Mer

Isolated: Yes