

2900 liters tank in Stainless 304



97 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: dent in the ornamental mantle; we can't give any guarantees about the agitator

Volumetric volume (L): 2.900 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no



Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 adjustable feet

Insulation material: Rockwool
Spray ball: RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Valve: RVS 304

Gasket shut-off valve (mat): unknown
Suitable for food industry: no
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 450 mm
Hinged lid: yes

Tank outlet: inside Ø 45 mm
Total outlet valve: no, optional
Agitator: yes
Agitator type: gate
Position engine: at the top

Insulation body: yes
Insulation thickness: 140
Internal diameter tank: 1.800 mm
Distance from outlet to ground: 360 mm
Outer diameter tank: 2.000 mm

Cylinder height: 1.160 mm
Total height of tank: 2.950 mm



SKU: 387677

Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: dent in the ornamental mantle; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 2900

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Tank Outlet: inside Ø 45 mm

Technical Drawing Available: No, it is not.



Material Overview

Material: Stainless steel 304

Insulation material: Rockwool

Tank Dimensions

Cylinder Height: 1.160 mm

Internal diameter: 1.800 mm

Outlet Height to Ground: 360 mm

Total Height: 2,950 mm

Outer diameter: 2,000 mm

Stirrer

Motor Position: at the top

Agitator Type: gate

Outer Cladding and Insulation Thickness

Jacket insulation: Yes

Insulation material: Rockwool

Mer

Insulation Thickness OW: 140

Isolated: Yes