

29250 liter tank in Syrafast 316



246 000 SEK /st exkl moms

Additional information: Manhole diameter: approx. 600 mm; saddles made of 1.4301 (stainless steel 304)

Volumetric volume (L): 29.250 L

Pressure in tank: vacuum

Max. pressure (Bar): 1 Bar



Min. pressure (Bar): 0,25 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: horizontal

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN100

Internal diameter tank: 2.400 mm

Total outer length: 6.800 mm

SKU: 475666

Mer information



Product Description

Material: Acid-resistant 316

Model: Horizontal

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: single-skin

Max. Service Temperature: 100 °C

Mobile Tank: No, it is not.

Övrig information: Manhole diameter: approx. 600 mmm; saddles made of Aisi 304

Agitator: No

Overpressure: 1 bar

Complete Drainage: Yes

Vacuum Pressure: 0,25 bar

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 29250

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Internal diameter: 2,400 mm

Mer

Isolated: No