300 liter tank in Acid-proof 316

72 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type VC-SLO
Volumetric volume (L): 300 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80
Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: large seperat lid

Shape of tank: cylindrical
Bottom type: conical 20 °
Total discharge: yes
Fixation points: 3 non adjustable feet
Fixation point(s): RVS 304L

Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no

CIP spray ball: no
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851 female
Total outlet valve: no, optional
Agitator: no

Top: 2 mm
Cylinder: 3 mm
Bottom: 3 mm
Distance from outlet to ground: 250 mm
Outer diameter tank: 703 mm

Cylinder height: 750 mm
Total height of tank: 1.283 mm
Empty weight tank: 75

SKU: 376637

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank: ATM – atmospheric
Stainless steel finish: 2b
Configuration: single-skin
Max. Service Temperature: 80 °C
Maximum Product Density: 1200
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Agitator: No
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage: Yes
Bottom Type: conical 20 °
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 300

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 40 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 female

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L

Tank Dimensions

Cylinder Height: 750 mm
Outlet Height to Ground: 250 mm
Total Height: 1.283 mm
Outer diameter: 703 mm

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm
Top: 2 mm

Mer

Isolated: No
Weight: 75

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor