

300 liter tank in Acid-proof 316



175 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-HICA

Additional information: example picture; delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm

Volumetric volume (L): 300 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic



Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: yes

Top type: half hinging lid °

Shape of tank: cylindrical

Bottom type: conical 10 °

Total discharge: yes

Fixation points: 4 casters

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Water pressure HE: 3 Bar

Hydraulic test pressure: 4 Bar

Working temperature HE cylinder: 130 °C

Heat exchanger: RVS 304

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: yes

CIP spray ball: no, optional

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Agitator: no, optional

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Cylinder: 2

Insulation body: yes

finish of the outer jacket: welded

Insulation thickness: 40

Outer diameter tank: 763 mm

Total height of tank: 1.760 mm

Empty weight tank: 136

SKU: 377156

Mer information



Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Newly manufactured

Operating Pressure in Tank:

Stainless steel finish: 2b

Configuration: isolert med varmeveksler

Max. Service Temperature: 100 °C

Maximum Product Density: 1200

Min. Operating Temperature: -10 °C

Mobile Tank: Yes

Övrig information: example picture; delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Additional Information2: Ra=<0.8µm

Agitator: No

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical 10 °

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 300

Equipment

Agitator flange: Yes

Nameplate: Yes

Food-grade: Yes

Tank Outlet: inside Ø 40 mm

Technical Drawing Available: Yes

Outlet Type: DIN11851



Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304
Insulation material: Rockwool
Exterior cladding: RVS 304

Tank Dimensions

Total Height: 1.760 mm
Outer diameter: 763 mm

Heat exchangers

Operating Temperature Heat Exchanger Cylinder: 130 °C
Bottom hydrostatic test pressure: 4 bars
Hydrostatic test pressure: 4 bars
Position värmeväxlare: the complete cylinder
Type of Heat Exchanger on Cylinder: dimple jacket
Water Pressure Heat Exchanger: 3 bars

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm
Top: 3 mm

Outer Cladding and Insulation Thickness

External jacket finish: welded
Jacket insulation: Yes
Insulation material: Rockwool



Mer

Heat Exchanger: RVS 304

Cylinder OW: 2

Insulation Thickness OW: 40

Isolated: No

Weight: 136