# 3000 liter tank in 304 stainless steel

107 000 SEK /st exkl moms

**Article type**: second-hand mixing tank
**Additional information**: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
**Volumetric volume (L)**: 3.000 L
**Pressure in tank**: ATM - atmosferic
**Material wet parts**: SS AISI 304 (V2A)

**Model**: vertical
**Configuration**: insulated with heat-exchanger
**Heat exchanger**: yes
**Insulation**: yes

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**Mobile tank**: no

**Top type**: conical
**Shape of tank**: cylindrical
**Bottom type**: conical
**Bottom outlet**: yes
**Total discharge**: yes

**Fixation points**: 3 adjustable feet
**Type of HE on the cylinder**: half pipe welded onto the outside of the innertank
**Position HE**: the complet cilinder
**Type of HE on the bottom**: half pipe welded onto the outside of the innertank
**Manway(s)**: RVS 304

**Gasket manway(s)**: unknown
**Fixation point(s)**: RVS 304
**Suitable for food industry**: yes
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: no
**Flange for agitator**: no
**Number of manways**: 1
**Position of manway**: at the top
**Height manhole 1 (mm)**: 350 mm x H 440 mm

**Hinged lid**: yes
**Tank outlet**: inside Ø 50 mm
**Agitator**: yes
**Agitator type**: propeller agitator
**Position engine**: at the top

**Power**: 2
**Voltage**: 380 V - three-phase
**Current**: 3,70
**Distance from outlet to ground**: 700 mm
**Outer diameter tank**: 1.700 mm

**Cylinder height**: 1.650 mm
**Total height of tank**: 3.000 mm

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**Empty weight tank**: 900

**SKU:** 416795

## Mer information

**Product Description**

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank:
Configuration: isolert med varmeveksler
Mobile Tank: No, it is not.
Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: conical
Heating / Cooling: Yes
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 3000



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

### Equipment
Product Dokument finns: No
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: No, it is not.

### Material Overview
Material: Stainless steel 304
Fixing point(s): RVS 304

### Tank Dimensions
Cylinder Height: 1.650 mm
Outlet Height to Ground: 700 mm
Total Height: 3,000 mm
Outer diameter: 1.700 mm

### Heat exchangers
Position värmeväxlare: the complete cylinder
Type of Heat Exchanger on Cylinder: half pipe welded onto the outside of the innertank
Bottom Heat Exchanger Type: half pipe welded onto the outside of the innertank

### Stirrer
Power (kW): 2
Motor Position: at the top
Agitator Type: propeller agitator
Voltage: 380 V – three-phase

### Mer
Isolated: Yes
Weight: 900

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor