

3000 liter tank in 304 stainless steel



108 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 3.000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 adjustable feet

Type of HE on the cylinder: half pipe welded onto the outside of the innertank

Position HE: the complet cilinder

Type of HE on the bottom: half pipe welded onto the outside of the innertank

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 350 mm x H 440 mm

Hinged lid: yes

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Power: 2

Voltage: 380 V - three-phase

Current: 3,70

Distance from outlet to ground: 700 mm

Outer diameter tank: 1.700 mm

Cylinder height: 1.650 mm

Total height of tank: 3.000 mm



Empty weight tank: 970

SKU: 417386

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 3000



Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 1.650 mm
Outlet Height to Ground: 700 mm
Total Height: 3,000 mm
Outer diameter: 1.700 mm

Heat exchangers

Position värmeväxlare: the complete cylinder
Type of Heat Exchanger on Cylinder: half pipe welded onto the outside of the innertank
Bottom Heat Exchanger Type: half pipe welded onto the outside of the innertank

Stirrer

Power (kW): 2
Motor Position: at the top
Agitator Type: propeller agitator
Voltage: 380 V – three-phase

Mer

Isolated: Yes
Weight: 970