3000 liter tank in 304 stainless steel

108 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Volumetric volume (L): 3.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Bottom outlet: yes
Total discharge: yes

Fixation points: 3 adjustable feet
Type of HE on the cylinder: half pipe welded onto the outside of the innertank
Position HE: the complet cilinder
Type of HE on the bottom: half pipe welded onto the outside of the innertank
Manway(s): RVS 304

Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Position of manway: at the top
Height manhole 1 (mm): 350 mm x H 440 mm
Hinged lid: yes

Tank outlet: inside Ø 50 mm
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top
Power: 1,50

Voltage: 380 V - three-phase
Current: 3,70
Distance from outlet to ground: 700 mm
Outer diameter tank: 1.700 mm
Cylinder height: 1.650 mm

Total height of tank: 3.600 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Empty weight tank: 970

SKU: 446627

Mer information

Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank:
Configuration: insulated with heat-exchanger
Mobile Tank: No, it is not.
Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: conical
Heating / Cooling: Yes
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 3000

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 1.650 mm
Outlet Height to Ground: 700 mm
Total Height: 3.600 mm
Outer diameter: 1.700 mm

Heat exchangers

Position värmeväxlare: the complete cylinder
Type of Heat Exchanger on Cylinder: half pipe welded onto the outside of the innertank
Bottom Heat Exchanger Type: half pipe welded onto the outside of the innertank

Stirrer

Power (kW): 1,50
Motor Position: at the top
Agitator Type: propeller agitator
Voltage: 380 V – three-phase

Mer

Isolated: Yes
Weight: 970

Rodervägen 57
891 78 Bonässund
info@processoverskott.se