

3000 liter tank in Acid-proof 316



120 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 3.000 L

Pressure in tank: ATM - atmosferic



Max. temperature (°C): 60 °C

Min. temperature (°C): 10 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Manway(s): RVS 316

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Hinged lid: yes

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Power: 3

Outer diameter tank: 1.400 mm

Cylinder height: 2.000 mm

Feet height: 1.200 mm



Total height of tank: 3.900 mm

SKU: 411614

Mer information

Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: single-skin

Max. Service Temperature: 60 °C

Min. Operating Temperature: 10 °C

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 3000



Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Tank Dimensions

Cylinder Height: 2,000 mm
Height on legs: 1.200 mm
Total Height: 3,900 mm
Outer diameter: 1.400 mm

Stirrer

Power (kW): 3
Motor Position: at the top
Agitator Type: propeller agitator

Mer

Isolated: No