

30000 liter tank in Acid-proof 316



318 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The tanks have never been used.; we can't give any guarantees about the agitator

Volumetric volume (L): 30.000 L

Max. density P (kg/m³): 1.000

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no



Insulation: no

Mobile tank: no

Top type: conical 10 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Wall type: conical 15 °

Total discharge: yes

Fixation points: 4 adjustable feet

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 316 (V4A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Tank outlet: inside Ø 65 mm

Total outlet valve: yes

Agitator: yes

Agitator type: propeller agitator

Position engine: in the cylinder

Power: 0,25

Voltage: three-phase

Outer diameter tank: 2.500 mm

Cylinder height: 6.000 mm

Total height of tank: 7.000 mm

Empty weight tank: 1.500

SKU: 488553



Mer information

Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Stainless steel finish: 2b

Configuration: single-skin

Maximum Product Density: 1000

Mobile Tank: No, it is not.

Övrig information: The tanks have never been used; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical 15 °

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 30000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 65 mm

Technical Drawing Available: No, it is not.

Outlet Valve: Yes



Material Overview

Material: Acid-resistant 316

Fixing point(s): RVS 304

Material vätskeberörd del på omrörare: SS AISI 316 (V4A)

Tank Dimensions

Cylinder Height: 6,000 mm

Total Height: 7,000 mm

Outer diameter: 2.500 mm

Stirrer

Power (kW): 0,25

Motor Position: in the cylinder

Agitator Type: propeller agitator

Voltage: three-phase

Mer

Isolated: No

Weight: 1.500