

30000 liters tank in Stainless 304



192 000 SEK /st exkl moms

Additional information: Wool fat; Manhole diameter approx. 580 mm; metallic discoloration inside in the area of the upper bottom; some residues of previous content; manhole cover plated

Volumetric volume (L): 30.000 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 70 °C



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 90 L

Max Overpressure: 6 Bar

Max. working temperature: 160 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: cylinder

Outlet of tank: flange DN125

Cylinder: 6,20 mm

Bottom: 6,60 mm

Internal diameter tank: 2.480 mm

Cylinder height: 5.980 mm

Total height of tank: 8.050 mm

Empty weight tank: 2.300

SKU: 422309



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 70 °C

Mobile Tank: No, it is not.

Övrig information: Wool fat; Manhole diameter approx. 580 mm; metallic discoloration inside in the area of the upper bottom; some residues of previous content; manhole cover plated

Agitator: No

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 30000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: Yes

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 5,980 mm

Internal diameter: 2,480 mm

Total Height: 8.050 mm

**Tjocklek på tank**

Bottom: 6,60 mm

Cylinder: 6,20 mm

Mer

Isolated: No

Weight: 2.300