

30000 liters tank in Stainless 304



144 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: Stainless steel tank with steel painted outer jacket. The outer jacket is insulated with 150mm PIR and cladded with screwed stainless steel plates.

Volumetric volume (L): 30.000 L

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: insulated



Heat exchanger: no

Insulation: yes

Mobile tank: no

Shape of tank: cylindrical

Wall type: conical

Total discharge: yes

Fixation points: 6 non adjustable feet

Insulation material: PIR

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Height manhole 1 (mm): 500 mm x H 390 mm

Tank outlet: inside Ø 70 mm

Agitator: no, optional

finish of the outer jacket: riveted

Insulation thickness: 150

Internal diameter tank: 2.880 mm

Distance from outlet to ground: 200 mm

Outer diameter tank: 3.200 mm

Cylinder height: 4.450 mm

Total height of tank: 3.500 mm

Total outer length: 5.800 mm

Empty weight tank: 4.000

SKU: 387290



Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Horizontal

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Stainless steel finish: 2b

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: Stainless steel tank with steel painted outer jacket. The outer jacket is insulated with 150mm PIR and clad with screwed stainless steel plates.

Agitator: No

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 30000

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 70 mm

Technical Drawing Available: No, it is not.



Material Overview

Material: Stainless steel 304

Insulation material: PIR

Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 4,450 mm

Internal diameter: 2.880 mm

Outlet Height to Ground: 200 mm

Total Height: 3.500 mm

Outer diameter: 3.200 mm

Outer Cladding and Insulation Thickness

External jacket finish: riveted

Insulation material: PIR

Mer

Insulation Thickness OW: 150

Isolated: Yes

Weight: 4.000