

30000 liters tank in Stainless 304



241 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 30.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no



Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 6 adjustable feet

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304L

Spray ball: RVS 304L

Manway(s): RVS 304L

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Hinged lid: yes

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Power: 1,50

Voltage: 380 V - three-phase

Internal diameter tank: 2.980 mm

Distance from outlet to ground: 1.900 mm

Outer diameter tank: 3.100 mm

Cylinder height: 4.300 mm

Total height of tank: 7.700 mm

SKU: 485855



Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 30000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 50 mm

Technical Drawing Available: No, it is not.



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Insulation material: Rockwool

Exterior cladding: RVS 304L

Tank Dimensions

Cylinder Height: 4.300 mm

Internal diameter: 2,980 mm

Outlet Height to Ground: 1.900 mm

Total Height: 7,700 mm

Outer diameter: 3.100 mm

Stirrer

Power (kW): 1,50

Motor Position: at the top

Agitator Type: propeller agitator

Voltage: 380 V – three-phase

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Isolated: Yes