

## 30000 liters tank in Stainless 304



200 000 SEK /st exkl moms

**Additional information:** Manhole approx. 345 x 445 mm; height-adjustable dome screws of the feet missing; bump at the insulation jacket; manhole cover is missing; pipe end cut flush

**Volumetric volume (L):** 30.000 L

**Pressure in tank:** ATM - atmospheric

**Max. temperature (°C):** 80 °C



**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** cylinder

**Outlet of tank:** 48

**Agitator:** yes

**Number of revolutions:** 20 / 41

**Power:** 1.2 / 2.2

**Internal diameter tank:** 2.880 mm

**Outer diameter tank:** 3.020 mm

**Total height of tank:** 6.700 mm

**SKU:** 486245

## Mer information



## Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Max. Service Temperature: 80 °C

Mobile Tank: No, it is not.

Övrig information: Dairy; Manhole approx. 345 x 445 mm; height-adjustable screws of the feet are missing; bump at the insulation jacket; manhole cover is missing; pipe end cut flush; we can't give any guarantees about

Additional Information2: the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 30000

## Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

## Material Overview

Material: Stainless steel 304

## Tank Dimensions

Internal diameter: 2.880 mm

Total Height: 6.700 mm

Outer diameter: 3,020 mm



## **Stirrer**

Power (kW): 1.2 / 2.2

Speed (RPM): 20 / 41

## **Mer**

Isolated: Yes