

30000 liters tank in Stainless 304



226 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 30.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no



Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 non adjustable feet

Manway(s): RVS 304
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Number of manways: 2
Position of manway: at the top
Height manhole 1 (mm): 500 mm

Position 2nd manway: cylinder
Height manhole 2 (mm): 340 x 430 mm
Tank outlet: inside Ø 100 mm
Outlet type: DIN11851
Agitator: yes

Agitator type: anchor
Position engine: at the top
Number of revolutions: 35
Power: 9,50
Voltage: three-phase

Top: 3 mm
Cylinder: 3 mm
Bottom: 4 mm
Distance from outlet to ground: 700 mm
Outer diameter tank: 3.000 mm

Cylinder height: 4.550 mm
Total height of tank: 7.000 mm
Empty weight tank: 2.000

SKU: 565892

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 30000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 100 mm

Technical Drawing Available: No, it is not.

Outlet Type: DIN11851



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 4,550 mm

Outlet Height to Ground: 700 mm

Total Height: 7,000 mm

Outer diameter: 3,000 mm

Stirrer

Power (kW): 9,50

Motor Position: at the top

Agitator Type: anchor

Speed (RPM): 35

Voltage: three-phase

Tjocklek på tank

Bottom: 4 mm

Cylinder: 3 mm

Top: 3 mm

Mer

Isolated: No

Weight: 2.000