

30400 liter tank in Acid-proof 316



395 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K5-SL

Additional information: inner surface 0.8μ

Volumetric volume (L): 30.400 L

Max. density P (kg/m³): 1.350

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C



Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 20 °

Total discharge: yes

Fixation points: 5 adjustable feet

Manway(s): RVS 316

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: TUV

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

CIP spray ball: no, optional

Tank outlet: inside Ø 80 mm

Outlet type: DIN11851 male

Total outlet valve: no, optional

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2 mm

Bottom: 4 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 2.984 mm

Cylinder height: 4.000 mm

Feet height: 1.005 mm

Total height of tank: 5.450 mm

Empty weight tank: 1.200

SKU: 385010

Mer information



Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank:
Stainless steel finish: 2b
Configuration: single-skin
Max. Service Temperature: 100 °C
Maximum Product Density: 1350
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Övrig information: inner surface 0.8μ
Agitator: No
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: conical 20 °
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 30400

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 80 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L



Tank Dimensions

Cylinder Height: 4,000 mm

Height on legs: 1.005 mm

Outlet Height to Ground: 400 mm

Total Height: 5.450 mm

Outer diameter: 2.984 mm

Tjocklek på tank

Bottom: 4 mm

Cylinder: 2 mm

Top: 2,50 mm

Mer

Isolated: No

Weight: 1.200