


3200 liters tank in Stainless 304



107 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K5-SL

Additional information: Ra=<0.8µm

Volumetric volume (L): 3.200 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C



Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 adjustable feet

Manway(s): RVS 304L

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: TUV

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 65 mm

Outlet type: DIN11851 male

Top: 2 mm

Cylinder: 2 mm

Bottom: 2 mm

Distance from outlet to ground: 289 mm

Outer diameter tank: 1.393 mm

Cylinder height: 2.000 mm

Height of top: 241 mm

Feet height: 576 mm



Total height of tank: 2.900 mm

Empty weight tank: 220

SKU: 381167

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Newly manufactured

Operating Pressure in Tank:

Stainless steel finish: 2b

Configuration: single-skin

Max. Service Temperature: 100 °C

Maximum Product Density: 1200

Min. Operating Temperature: -10 °C

Mobile Tank: No, it is not.

Övrig information: Ra=<0.8µm

Agitator: No

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304L (V2A)

Volume in liters: 3200



Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 65 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304L

Tank Dimensions

Cylinder Height: 2,000 mm
Height on legs: 576 mm
Outlet Height to Ground: 289 mm
Total Height: 2,900 mm
Outer diameter: 1,393 mm

Tjocklek på tank

Bottom: 2 mm
Cylinder: 2 mm
Top: 2 mm

Mer

Isolated: No
Weight: 220