

32000 liters tank in Stainless 304



320 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The tank has never been used.

Volumetric volume (L): 32.000 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 60 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 304L (V2A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 13 °

Shape of tank: cylindrical

Bottom type: conical 20 °

Total discharge: yes

Fixation points: 4 non adjustable feet

Manway(s): RVS 304L

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Hinged lid: yes

Tank outlet: inside Ø 80 mm

Outlet type: DIN11851 male

Total outlet valve: no, optional

Top: 2 mm

Cylinder: 2 mm

Bottom: 4 mm

Distance from outlet to ground: 395 mm

Outer diameter tank: 2.984 mm

Cylinder height: 4.500 mm

Total height of tank: 5.872 mm

Empty weight tank: 1.250



SKU: 480507

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Stainless steel finish: 2b

Configuration: single-skin

Max. Service Temperature: 60 °C

Maximum Product Density: 1200

Min. Operating Temperature: -10 °C

Mobile Tank: No, it is not.

Övrig information: The tank has never been used.

Agitator: No

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical 20 °

Heating / Cooling: No

Contact Surface: SS AISI 304L (V2A)

Volume in liters: 32000



Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 80 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304L

Tank Dimensions

Cylinder Height: 4.500 mm
Outlet Height to Ground: 395 mm
Total Height: 5.872 mm
Outer diameter: 2.984 mm

Tjocklek på tank

Bottom: 4 mm
Cylinder: 2 mm
Top: 2 mm

Mer

Isolated: No
Weight: 1.250