

3331 liter tank in Syrafast 316



204 000 SEK /st exkl moms

Additional information: 1 immersion sleeve for PT 100 probe inside the tank

Volumetric volume (L): 3.331 L

Pressure in tank: pressure

Max. temperature (°C): 120 °C



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 17 L

Max Overpressure: 3 Bar

Max. working temperature: 120 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.596 mm

Outer diameter tank: 1.800 mm

Cylinder height: 1.500 mm

Total height of tank: 2.720 mm

Empty weight tank: 1.200

SKU: 419249



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Max. Service Temperature: 120 °C

Mobile Tank: No, it is not.

Övrig information: 1 immersion sleeve for PT 100 probe inside the tank; we can't give any guarantees about the heating/cooling jacket

Agitator: No

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 3331

Equipment

Product Dokument finns: No, it is not.

Agitator flange: Yes

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 1.500 mm

Internal diameter: 1.596 mm

Total Height: 2,720 mm

Outer diameter: 1.800 mm



Tjocklek på tank

Bottom: 3 mm

Cylinder: 3 mm

Top: 2,50 mm

Mer

Isolated: Yes

Weight: 1.200