

3500 liter tank in Acid-proof 316



106 000 SEK /st exkl moms

Additional information: rennet-production; Feet originally stood on load cells, these are no longer present (see photos); according to the rating plate, the heating coil is designed for an operating pressure of 3 bar at a temperature of - 5° C (see photos on rating plate); manhole diameter 430 mm; suspension of the manhole cover incomplete

Volumetric volume (L): 3.500 L



Pressure in tank: pressure

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 62 L

Max Overpressure: 3 Bar

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN40 DIN 11851

Agitator: yes

Number of revolutions: 910

Power: 0,55

Internal diameter tank: 1.350 mm

Outer diameter tank: 1.560 mm

Cylinder height: 2.500 mm

Total height of tank: 3.450 mm

SKU: 395066



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: rennet-production; Feet originally stood on load cells, these are no longer available (see pictures); according to the type plate, the heating coil is designed for an operating pressure of 3 bar at

Additional Information2:

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 3500

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 2.500 mm
Internal diameter: 1.350 mm
Total Height: 3.450 mm
Outer diameter: 1,560 mm

Stirrer

Power (kW): 0,55
Speed (RPM): 910

Mer

Heat Exchanger: RVS 304
Isolated: Yes