

3533 liter tank in Stainless 304



110 000 SEK /st exkl moms

Additional information: Double jacket with electric plug-in heater : 9 kW (incomplete; no guarantee of functionality); presumably the lower cylinder area of the vessel can also be heated; manhole approx. 310 x 420 mm; internal fittings (e.g. welded tabs) inside the tank; some residues of previous content

Volumetric volume (L): 3.533 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 553 L

Max. working temperature: 50 °C

Type HE on the bottom: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 76

Power: 1,50

Internal diameter tank: 1.490 mm

Outer diameter tank: 1.650 mm

Cylinder height: 1.980 mm

Total height of tank: 3.200 mm

SKU: 414359



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Max. Service Temperature: 50 °C

Mobile Tank: No, it is not.

Övrig information: Pharmacy; Double jacket with electric plug-in heater: 9 kW (incomplete; functionality not guaranteed); presumably the lower cylinder area of the tank can also be heated; manhole approx. 310 x 420

Additional Information2:

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 3533

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 1.980 mm
Internal diameter: 1.490 mm
Total Height: 3.200 mm
Outer diameter: 1.650 mm

Stirrer

Power (kW): 1,50
Speed (RPM): 76

Mer

Heat Exchanger: RVS 304
Isolated: Yes